




NOTES:

1. SUGGESTED MOUNTING HOLE = $\phi.117 \pm .002$
2. MAXIMUM INSTALLATION TEMP.: 500°F



LEAD FINISH: SILVER	
EYELET FINISH: SOLDER	
CAPACITANCE	50pF-175pF
TEMP. RANGE	-25°C TO 85°C
CURRENT	15 AMP MAX.
WORKING VOLTAGE	85°C 100 VDC MAX.
D.C. RESISTANCE	.01ohms MAX.
MIN. I.L. PER MIL-STD-220 AT 25°C NO LOAD	
FREQ. MHz	I.L. (db)
1000	16
SCHEMATIC 	
MARKING: PART: NONE	
BAG: SCI	
51-713-095	
DATE CODE	
LOT#	
QTY/BAG (200 MAX.)	

						 SPECTRUM CONTROL INC. ERIE, FAIRVIEW PENNSYLVANIA
		0	REV. NO.	TOLERANCES UNLESS OTHERWISE SPECIFIED		
		880088	CHANGE NOTICE	Fractions $\pm 1/64$	Dwn. KRDZALIC	
				Dec. .xx \pm	Ckd. 2/7/01	
				Dec. .xxx $\pm .010$	Description	
				Angles $\pm 0^{\circ} 30'$	Pi SOLDER-IN FILTER	
				CODE IDENT. NO. DLSP2	Apvd.	
					Scale NONE	
						51-713-095