
KEMET Part Number: B45196L1107K409 Obsolete

(T495D107K006ZTA800)



B45196L, Tantalum, MnO2 Tantalum, 100 uF, 10%, 6.3 V, SMD, Molded, Automotive, 800 mOhms, 7343, Height Max = 3.1mm



| Dimensions | | |
|------------|----------------|--|
| Footprint | 7343 | |
| L | 7.3mm +/-0.3mm | |
| W | 4.3mm +/-0.3mm | |
| Н | 2.8mm +/-0.3mm | |
| S | 1.3mm +/-0.3mm | |
| F | 2.4mm +/-0.1mm | |
| K | 1.8mm TYP | |

| Packaging Specifications | | |
|--------------------------|------------|--|
| Packaging: | T&R, 178mm | |
| Packaging Quantity: | 750 | |

| General Information | |
|---------------------|-------------------------|
| Supplier: | KEMET |
| Series: | B45196L |
| Dielectric: | MnO2 Tantalum |
| Style: | SMD Chip |
| Description: | SMD, Molded, Automotive |
| Features: | Automotive |
| RoHS: | Yes |
| Termination: | Tin |
| Qualifications: | AEC-Q200 |
| AEC-Q200: | Yes |
| Miscellaneous: | AEC-Q200 |
| Notes: | Obsolete |

| Specifications | | |
|------------------------|---|--|
| Capacitance: | 100 uF | |
| Capacitance Tolerance: | 10% | |
| Voltage DC: | 6.3 VDC (85C), 4.22 VDC (125C) | |
| Temperature Range: | -55/+125C | |
| Rated Temperature: | 85C | |
| Dissipation Factor: | 8% | |
| Failure Rate: | N/A | |
| Resistance: | 0.8 Ohms (100kHz) | |
| Current: | 129.1 mAmps (25C), 116.2 mAmps (85C), 51.6 mAmps (125C) | |
| Leakage Current: | 6.3 uA | |

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

